

WOODS Box Fans





BOX FAN Application

Box fans are used in commercial complexes where a fan needs to be placed with a ducted system to maintain the pressure within the system for proper ventilation.



Offices &
Kitchens

CONTENTS	PAGE
ESTOC TARGE	2
Product Facts	2
Performance & Electrical Data	3
Drawings and Dimensions	4
Performance Charts	5
Construction Scheme	9
Wiring Diagrams	10
ESTOC TARGE EC	12
Product Facts	12
Performance & Electrical Data	13
Drawings and Dimensions	14
Performance Charts	15
Construction Scheme	18
Wiring Diagrams	19
ePOWERBOX AC	20
Product Facts	20
Performance & Electrical Data	21
Drawings and Dimensions	22
Performance Charts	23
Installation Guide	27
Construction Scheme	28
Wiring Diagrams	29
ePOWERBOX EC	30
Product Facts	30
Performance & Electrical Data	31
Drawings and Dimensions	32
Performance Charts	33
Installation Guide	36
Construction Scheme	37
Wiring Diagrams	38
KATANA EC	40
Product Facts	40
Performance & Electrical Data	41
Drawings and Dimensions	42
Performance Charts	43
Construction Scheme	46
Wiring Diagrams	47



PRODUCT FACTS

- Air flow up to 5.7 m³/s
- Static pressures up to 1400 Pa
- Speed controllable external rotor motors
- Multiple outlet orientations motor located out of air stream
- Air discharged at 90 degrees
- DW172 compliant for solid fuel cooking applications

ELECTRICAL SUPPLY

220-240V/50Hz/1PH & 380-420V/50Hz/3PH

TEMPERATURE RANGE

Up to 110°C depending on size, see electrical data table on next page for more information.

SIZES

355, 400, 450, 500, 560 and 630 mm

CONSTRUCTION

The casing is galvanized and made from sheet steel with double chambered aluminum supporting frames and plastic made corners. The acoustic insulation is made from fibre glass with a thickness of 20 mm. Can be horizontal or vertical mounted with weather proof hood and has removable side panels. One side of the casing is open as standard.

IMPELLER

The Estoc Targe is equipped with high efficiency backward curved centrifugal impellers made of aluminum.

MOTOR


Motor is situated out of air stream. The fans are equipped with direct driven external motors having motor protection through thermal contacts in the motor windings. The impellers together with the external rotor motors are dynamically balanced to quality standard G2,5 DIN ISO 19410.

SPEED CONTROLLER

Speed is variable using auto transformers and inverter control with auxiliary electronic control option and includes a integrated emergency switch.

Up to

110



PRODUCT CODE

Estoc Targe 50-355-3

- ESTOC TARGE - Product Name
- 50 = Box Size ie, 50 = 500mm; 67 =670mm; 80 = 800mm; 102 = 1020mm
- 355 = Spigot Diameter size (mm)
- 1 = 1PH or 3 = 3PH

ACCESSORIES

The range of accessories include dampers, flexible connectors, service doors, outlet covers, guards, side covering and insulating connections. A quick reference guide is shown below.



220-240V/50Hz/1PH & 380-420V/50HZ/3PH

Performance Table

Product Code	0	50	100	150	200	250	300	350	400	450	500	550	600	650
Estoc Targe 50-355-1	0.80	0.73	0.66	0.59	0.53	0.44	0.35	0.22	0.08					
Estoc Targe 67-400-1	1.26	1.20	1.12	1.03	0.93	0.83	0.73	0.62	0.49	0.28	0.09			
Estoc Targe 67-450-1	1.77	1.71	1.64	1.56	1.48	1.40	1.30	1.20	1.12	1.01	0.87	0.75	0.55	0.25

Product Code	m3/s @ Pa (Static)																							
	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	900	1000	1100	1200	1300	1400	
Estoc Targe 50-355-3	0.85	0.79	0.72	0.63	0.53	0.44	0.32	0.18	0.04															
Estoc Targe 67-400-3	1.25	1.17	1.09	1.00	0.87	0.76	0.69	0.51	0.37	0.17														
Estoc Targe 67-450-3	1.81	1.73	1.66	1.59	1.52	1.45	1.35	1.25	1.14	1.03	0.90	0.74	0.56	0.22										
Estoc Targe 80-500-3	2.50	2.41	2.33	2.24	2.18	2.07	1.99	1.88	1.77	1.65	1.53	1.39	1.25	1.05	0.83	0.56	0.26							
Estoc Targe 80-560-3	3.06	3.01	2.94	2.87	2.79	2.73	2.66	2.58	2.51	2.43	2.34	2.24	2.13	2.01	1.87	1.72	1.55	0.80						
Estoc Targe 80-630-3	3.97	3.90	3.84	3.77	3.70	3.62	3.55	3.46	3.37	3.29	3.20	3.11	3.00	2.89	2.77	2.64	2.52	2.30	2.06	1.71	0.72	0.19		
Estoc Targe 102-630-3	5.75	5.66	5.57	5.48	5.39	30.30	5.19	5.10	4.99	4.88	4.77	4.66	4.54	4.41	4.28	4.14	3.98	3.63	3.27	2.80	2.19	1.55	0.32	


Product and Electrical Details

Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers		Maximum Operating Temp °C	Breakout *Sound Level db(A) (3m)
					Motor (kW)	Full Load Current (A)	Starting Current (A)		Transformer	Inverter		
Estoc Targe 50-355-1	GF503551	1360	Integral	220-240 V/50 Hz/1 Ph	0.3	1.4	3.5	CD3006	ME1.3	TEID 1.5	110	35
Estoc Targe 67-400-1	GF674001	1270	Integral	220-240 V/50 Hz/1 Ph	0.5	2.2	4.8	CD3006	ME1.3	TEID 2.2	90	39
Estoc Targe 67-450-1	GF674501	1380	Integral	220-240 V/50 Hz/1 Ph	1	5.4	12	CD3006	ME1.6	TEID 5	80	44

Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers		Maximum Operating Temp °C	Breakout *Sound Level db(A) (3m)
					Motor (kW)	Full Load Current (A)	Starting Current (A)		Transformer	Inverter		
Estoc Targe 50-355-3	GF535524	1360	Integral	380-420 V/50 Hz/3 Ph	0.3	0.7	2.6	CD3031	TDID 2.5	IDDXF54 2.2	110	35
Estoc Targe 67-400-3	GF674003	1240	Integral	380-420 V/50 Hz/3 Ph	0.5	1	2.8	CD3031	TDID 2.5	IDDXF54 2.2	100	38
Estoc Targe 67-450-3	GF674503	1380	Integral	380-420 V/50 Hz/3 Ph	0.9	1.8	8.8	CD3031	TDID 2.5	IDDXF54 2.2	100	44
Estoc Targe 80-500-3	GF805003	1380	Integral	380-420 V/50 Hz/3 Ph	1.5	3	15	CD3032	TDID 4	IDDXF54 3.7	90	47
Estoc Targe 80-560-3	GF805607	1410	Integral	380-420 V/50 Hz/3 Ph	2.5	5	35	CD3032	-	IDDXF54 7.2	100	49
Estoc Targe 80-630-3	GF806303	1445	Integral	380-420 V/50 Hz/3 Ph	4.4	8	46	CD3032	-	IDDXF54 9	90	53
Estoc Targe 102-630-3	GF163027	1460	Integral	380-420 V/50 Hz/3 Ph	6	11	62.6	CD3032	-	IDDXF54 12	75	91

*Sound power levels are average dBA at 3 metres distance over sphere, under free field conditions and are presented for comparative purposes only. Values shown are those at the mid-point of the performance curve. **For speed controllers, please refer to accessories section. For ErP efficiency ratings and grades please refer to our Fan Selector for more information.


Drawings and Dimensions




Product Code	A	B	C	D1	D2	E	F	G	Weight Max (kg)
Estoc Targe 50-355	420	420	500	228	350	218	398	360	35
67-400	500	590	670	248	422	258	568	450	52
67-450	500	590	670	289	422	258	568	450	69
80-500	590	720	800	310	519	338	698	580	78
80-560	740	720	800	362	519	338	698	580	106
80-630	800	720	800	405	560	338	698	580	146
102-630	880	940	1020	390	640	398	918	750	173

Performance charts


ESTOC TARGE 50-355-1 - GF503551



ESTOC TARGE 67-400-1 - GF674001




ESTOC TARGE 67-450-1 - GF674501




Drawings and Dimensions


ESTOC TARGE 50-355-3 - GF535524



ESTOC TARGE 67-400-3 - GF674003




ESTOC TARGE 67-450-3 - GF674503




Performance charts


ESTOC TARGE 80-500-3 - GF805003



ESTOC TARGE 80-560-3 - GF805607




ESTOC TARGE 80-630-3 - GF806303




Performance Charts

ESTOC TARGE 102-630-3 - GF163027



INSTALLATION GUIDE


Outdoor installation PowerBox GF Estoc Targe
Axial air flow (90° discharge available)
All accessories supplied separately



When the Estoc Targe is used externally with a horizontal outlet an additional weather roof/cowl is available if required.

Construction Scheme

INDOOR INSTALLATION




OUTDOOR INSTALLATION



Wiring Diagrams - Estoc Targe

CD3006




CD3031

CD3032

355-450

500-630



SELECTION TOOLS AND WEB RESOURCES

Guaranteed to
make your job easier

Woods Air Movement is committed to provide the best possible pre and post sales service. We are proud of our products and continuously invest in our selection tools and sales support staff to make sure you always get the best from them.



- Product technical documentation
- Instruction manuals
- Certifications
- Sales and marketing leaflets
- And more...

We also provide BIM files for many Woods Air Movement products as well as MagiCAD plugin.

ALWAYS AVAILABLE AT
www.woodsairmovement.com
your first port of call for up-to-date

Selection tools at your service
We offer a number of advanced selection tools and apps, available directly to download from www.woodsairmovement.com, that will help you make the correct product choice for every application and provide guidance to your customers. Among the tools you will find are **ACON** for Air Treatments, **SELECT** for Air Diffusion and **FAN SELECTOR** for Air Movement products

PRODUCT FACTS

- Air flow up to 3.7 m3/s
- Static pressures up to 1000 Pa
- Controllable EC motors
- Multiple outlet orientations motor located out of air stream
- Air discharged at 90 degrees
- DW172 compliant for solid fuel cooking applications

ELECTRICAL SUPPLY

220-240V/50Hz/1PH & 380-420V/50Hz/3PH

TEMPERATURE RANGE

Up to 120°C depending on size, see electrical data table on next page for more information.

SIZES

355, 400, 450, 500, 560 and 630 mm

CONSTRUCTION

The casing is galvanized and made from sheet steel with double chambered aluminum profiles and plastic made corners. The acoustic insulation is made from fibre glass with a thickness of 20 mm. Can be horizontal or vertical mounted with weather proof hood and has removable side panels. One side of the casing is open as standard.

IMPELLER

The Estoc Targe is equipped with high efficiency backward curved centrifugal impellers made of aluminum.

MOTOR


Motor is situated out of air stream. The fans are equipped with direct driven external motors having motor protection through thermal contacts in the motor windings. The impellers together with the external rotor motors are dynamically balanced to quality standard G2,5 DIN ISO 19410.

SPEED CONTROLLER

Speed is variable using a 0-10 volt potentiometer.

Up to

110



PRODUCT CODE

Estoc Targe EC 50-355-3

- ESTOC TARGE EC - Product Name
- 50 = Box Size ie, 50 = 500mm; 67 = 670mm; 80 = 800mm; 102 =1020mm
- 355 = Spigot Diameter size (mm)
- 1 = 1PH or 3 = 3PH

ACCESSORIES

The range of accessories include dampers, flexible connectors, service doors, outlet covers, guards, side covering and insulating connections. A quick reference guide is shown below.



220-240V/50Hz/1PH & 380-420V/50HZ/3PH

Performance Table

Product Code	m³/s @ Pa (Static)										
	0	100	200	300	400	500	600	700	800	900	1000
Estoc Targe EC 50-355-1	0.90	0.81	0.69	0.55	0.19						
Estoc Targe EC 67-400-1	1.25	1.13	0.98	0.78	0.37						
Estoc Targe EC 67-450-1	1.57	1.43	1.28	1.08	0.74						

Product Code	m³/s @ Pa (Static)										
	0	100	200	300	400	500	600	700	800	900	1000
Estoc Targe EC 50-355-3	0.91	0.80	0.69	0.55	0.21						
Estoc Targe EC 67-400-3	1.41	1.31	1.20	1.05	0.86	0.58					
Estoc Targe EC 67-450-3	1.79	1.67	1.54	1.39	1.20	0.91	0.13				
Estoc Targe EC 80-500-3	2.50	2.37	2.23	2.07	1.88	1.63	1.39	1.02	0.01		
Estoc Targe EC 80-560-3	3.03	2.88	2.74	2.59	2.41	2.23	2.01	1.74	1.00		
Estoc Targe EC 80-630-3	3.68	3.52	3.37	3.21	3.06	2.89	2.70	2.49	2.20	1.74	0.41

Product and Electrical Details


Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers	Maximum Operating Temp°C	Breakout
					Motor (kW)	Full Load Current (A)	Starting Current (A)		Potentiometer		*Sound Level db(A) (3m)
Estoc Targe EC 50-355-1	GF503555	1500	Integral	220-240 V/50 Hz/1 Ph	0.36	1.5	1.5	1.451	0-10 V Pot	120	36
Estoc Targe EC 67-400-1	GF674005	1320	Integral	220-240 V/50 Hz/1 Ph	0.43	1.8	1.8	1.451	0-10 V Pot	120	41
Estoc Targe EC 67-450-1	GF674506	1230	Integral	220-240 V/50 Hz/1 Ph	0.65	2.8	2.8	1.451	0-10 V Pot	120	42

Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers	Maximum Operating Temp°C	Breakout
					Motor (kW)	Full Load Current (A)	Starting Current (A)		Potentiometer		*Sound Level db(A) (3m)
Estoc Targe EC 50-355-3	GF503556	1500	Integral	380-420 V/50 Hz/3 Ph	0.36	0.7	0.7	1.451	0-10 V Pot	120	37
Estoc Targe EC 67-400-3	GF674006	1500	Integral	380-420 V/50 Hz/3 Ph	0.62	1.2	1.2	1.451	0-10 V Pot	120	43
Estoc Targe EC 67-450-3	GF674507	1400	Integral	380-420 V/50 Hz/3 Ph	0.95	1.7	1.7	1.451	0-10 V Pot	120	45
Estoc Targe EC 80-500-3	GF805006	1400	Integral	380-420 V/50 Hz/3 Ph	1.45	2.4	2.4	1.451	0-10 V Pot	120	48
Estoc Targe EC 80-560-3	GF805608	1400	Integral	380-420 V/50 Hz/3 Ph	2.3	3.6	3.6	1.451	0-10 V Pot	120	50
Estoc Targe EC 80-630-3	GF806306	1350	Integral	380-420 V/50 Hz/3 Ph	3.6	5.5	5.5	1.451	0-10 V Pot	120	51

*Sound power levels are average dBA at 3 metres distance over sphere, under free field conditions and are presented for comparative purposes only. Values shown are those at the mid-point of the performance curve. **For speed controllers, please see pages 250-297. For ErP efficiency ratings and grades please refer to our Fan Selector for more information.




Drawings and Dimensions




Product Code	A	B	C	D1	D2	E	F	G	Weight Max (kg)
Estoc Targe EC 50-355	540	420	500	228	348	218	398	360	44
67-400	600	590	670	248	422	258	568	450	60
67-450	600	590	670	289	422	258	568	450	66
80-500	740	720	800	310	519	338	698	580	96
80-560	740	720	800	362	519	338	698	580	102
80-630	740	720	800	405	560	338	698	580	112

Performance charts


ESTOC TARGE EC 50-355-1 - GF503555



ESTOC TARGE EC 67-400-1 - GF674006




ESTOC TARGE EC 67-450-1 - GF674506




Performance charts


ESTOC TARGE EC 50-355-3 - GF503556



ESTOC TARGE EC 67-400-3 - GF674006




ESTOC TARGE EC 50-355-3 - GF503556




Performance charts


ESTOC TARGE EC 67-400-3 - GF674006



ESTOC TARGE EC 80-560-3 - GF805608




ESTOC TARGE EC 80-630-3 - GF806306




Construction Scheme

INDOOR INSTALLATION




OUTDOOR INSTALLATION




Wiring Diagrams - Estoc Targe EC

CD3011



CD3012



PRODUCT FACTS

- Air flow up to 5.2 m3/s
- Static pressures up to 1130 Pa
- Speed controllable external rotor motors
- Multiple outlet orientations
- All panels interchangeable to offer flexible outlet position

ELECTRICAL SUPPLY

220-240V/50Hz/1PH & 380-420V/50Hz/3PH

TEMPERATURE RANGE

Maximum temperature from +40°C to +70°C (depending on the model)

SIZES

355, 400, 450, 500, 560, 630 and 710 mm

CONSTRUCTION

The ePowerBox AC casing is made from galvanized sheet steel with double chambered aluminum supporting frames and plastic made corners. The acoustic insulation made from mineral wool with a thickness of 20 mm.

IMPELLER

The ePowerBox AC has a backward curved centrifugal impellers made of plastic with galvanised steel support plates for those up to 560 mm. Fans with a diameter of 630 mm and larger have high efficiency backward curved centrifugal impellers made of aluminium.

MOTOR

The impellers together with the external rotor motors are dynamically balanced to quality standard G2,5 DIN ISO 19410.

SPEED CONTROLLER

Speed is 100% infinitely variable using auto transformers or inverter control.

NB; Performance reduction in straight through configuration. Please refer to performance curve.



PRODUCT CODE

ePowerBox AC 50-355-3

- ePowerBox AC - Product Name
- 50 = Box Size ie, 50 = 500mm; 67 = 670mm; 80 = 800mm; 102 = 1020mm
- 355 = Spigot Diameter size (mm)
- 1 = 1PH or 3 = 3PH

ACCESSORIES

The range of accessories include dampers, flexible connectors, service doors, outlet covers, guards, side covering and insulating connections. A quick reference guide is shown below.



220-240V/50Hz/1PH & 380-420V/50Hz/3PH

Performance Table

Product Code	m3/s @ Pa (Static)										
	0	100	200	300	400	500	600	700	800	900	1000
ePowerBox AC 50-355-1	0.91	0.79	0.66	0.45							
ePowerBox AC 67-400-1	1.30	1.17	1.04	0.87	0.58						
ePowerBox AC 67-450-1	1.91	1.77	1.61	1.44	1.21	0.91	0.13				
ePowerBox AC 67-500-1	2.61	2.43	2.24	2.04	1.83	1.55	1.16	0.40			

Product Code	m3/s @ Pa (Static)										
	0	100	200	300	400	500	600	700	800	900	1000
ePowerBox AC 50-355-3	0.92	0.80	0.66	0.43							
ePowerBox AC 67-400-3	1.29	1.15	1.01	0.81	0.40						
ePowerBox AC 67-450-3	1.81	1.66	1.49	1.29	1.03	0.59	0.03				
ePowerBox AC 67-500-3	2.58	2.40	2.23	2.03	1.81	1.55	1.16	0.39			
ePowerBox AC 80-560-3	3.61	3.40	3.19	2.98	2.75	2.47	2.13	1.69	0.88	0.21	
ePowerBox AC 80-630-3	4.03	3.84	3.65	3.44	3.28	3.05	2.84	2.56	2.24	1.73	0.09
ePowerBox AC 102-710-3	4.81	4.47	4.06	3.63	3.13	2.59	0.92				

Product and Electrical Details


Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers	Maximum Operating Temp°C	Breakout
					Motor (kW)	Full Load Current (A)	Starting Current (A)		Transformer		*Sound Level db(A) (3m)
ePowerBox AC 50-355-1	BE355017	1325	Integral	220-240 V-50 Hz-1 Ph	0.28	1.35	4.46	CD3028	TEID 1.5	65	33
ePowerBox AC 67-400-1	BE400018	1360	Integral	220-240 V-50 Hz-1 Ph	0.51	2.45	7.11	CD3028	TEID 2.2	65	45
ePowerBox AC 67-450-1	BE450022	1270	Integral	220-240 V-50 Hz-1 Ph	0.85	4.1	15.58	CD3028	TEID 3.5	45	41
ePowerBox AC 67-500-1	BE500003	1310	Integral	220-240 V-50 Hz-1 Ph	1.38	6.22	19.90	CD3028	TEID 7.5	40	45

Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers	Maximum Operating Temp°C	Breakout
					Motor (kW)	Full Load Current (A)	Starting Current (A)		Transformer		*Sound Level db(A) (3m)
ePowerBox AC 50-355-3	BE355018	1355	Integral	380-420V-50 Hz-3 Ph	0.28	0.67	2.68	CD3030	IDDXF54 2.2	70	34
ePowerBox AC 67-400-3	BE400019	1335	Integral	380-420V-50 Hz-3 Ph	0.44	0.88	3.34	CD3030	IDDXF54 2.2	70	37
ePowerBox AC 67-450-3	BE450023	1345	Integral	380-420V-50 Hz-3 Ph	0.73	1.47	4.85	CD3030	IDDXF54 2.2	50	37
ePowerBox AC 67-500-3	BE500004	1380	Integral	380-420V-50 Hz-3 Ph	1.29	2.82	14.95	CD3030	IDDXF54 3.7	60	44
ePowerBox AC 80-560-3	BE560023	1350	Integral	380-420V-50 Hz-3 Ph	2.1	4.07	16.28	CD3030	IDDXF54 5.3	50	47
ePowerBox AC 80-630-3	BI101234	1380	Integral	380-420V-50 Hz-3 Ph	3.28	6.1	34.20	CD3030	IDDXF54 7.2	60	55
ePowerBox AC 102-710-3	BI101237	890	Integral	380-420V-50 Hz-3 Ph	2.17	4.79	19.16	CD3030	IDDXF54 5.3	70	49

*Sound power levels are average dBA at 3 metres distance over sphere, under free field conditions and are presented for comparative purposes only. Values shown are those at the mid-point of the performance curve.

** For speed controllers, please refer to accessories section. For ErP efficiency ratings and grades please refer to our Fan Selector for more information.


Drawings and Dimensions




Product Code	A	B	C	D1	D2	G	Weight Max (kg)
ePowerbox 50-355	500	450	450	228	320	409	32
67-400	670	620	620	257	356	579	48
67-450	670	620	620	286	395	579	50
67-500	670	620	620	325	438	579	60
80-560	800	720	720	365	490	659	95
80-630	800	720	720	410	541	659	105
102-710	1020	940	940	460	605	879	146

Performance charts

ePOWERBOX AC 50-355-1 - BE355017




ePOWERBOX AC 67-400-1 - BE400018




Please note : -
The performances shown are based on the centrifugal 90 degrees discharge, for the axial flow performance please contact our sales team.

ePOWERBOX AC 67-450-1 BE450022




Performance charts

ePOWERBOX AC 67-500-1 - BE500003




ePOWERBOX AC 50-355-3 - BE355018




Please note : -
The performances shown are based on the centrifugal 90 degrees discharge, for the axial flow performance please contact our sales team.

ePOWERBOX AC 67-400-3 - BE400019




Performance charts

ePOWERBOX AC 67-450-3 - BE450019




ePOWERBOX AC 67-500-3 - BE500004




Please note : -
The performances shown are based on the centrifugal 90 degrees discharge, for the axial flow performance please contact our sales team.

ePOWERBOX AC 67-560-3 - BE560023




Performance charts

ePOWERBOX AC 80-630-3 - BI101234




ePOWERBOX AC 102-710-3 - BI101237




Please note : -
The performances shown are based on the centrifugal 90 degrees discharge, for the axial flow performance please contact our sales team.

Installation guide




Outdoor installation PowerBox Estoc
Axial air flow (90° discharge available)
All accessories supplied separately




Construction Scheme

Indoor installation:





Outdoor installation:





Wiring Diagrams - ePowerBox AC

CD 3028



CD 3030



PRODUCT FACTS

- Air flow up to 5.4 m3/s
- Static pressures up to 840 Pa
- Controllable EC motors
- Multiple outlet orientations

ELECTRICAL SUPPLY

220-240V/50Hz/1PH & 380-420V/50Hz/3PH

TEMPERATURE RANGE

Maximum temperature up to +55°C (depending on the model)

SIZES

315, 355, 400, 450, 500, 560, 630 and 710 mm

CONSTRUCTION

The ePowerBox EC casing is galvanized and made from sheet steel with with double chamber aluminum profiles and corners made of plastic and acoustic insulation made from fibre glass mats with a thickness of 20 mm. One side of the casing is open as standard.

IMPELLER

The ePowerBox EC has a backward curved centrifugal impellers made of plastic with galvanised steel support plates for those up to 560 mm. Fans with a diameter of 630 mm and larger have high efficiency backward curved centrifugal impellers made of aluminium.

MOTOR

The impellers together with the EC (electronically controlled) external rotor motors are dynamically balanced to quality standard G2,5 DIN ISO 19410.

SPEED CONTROLLER

Speed is variable using a 0-10 volt potentiometer.



PRODUCT CODE

ePowerBox EC 50-355-3

- ePowerBox EC - Product Name
- 50 = Box Size ie, 50 = 500mm; 67 = 670mm; 80 = 800mm; 102 = 1020mm
- 355 = Spigot Diameter size (mm)
- 1 = 1PH or 3 = 3PH 1020mm

ACCESSORIES

The range of accessories include dampers, flexible connectors, service doors, outlet covers, guards, side covering and insulating connections. A quick reference guide is shown below.



220-240V/50Hz/1PH & 380-420V/50HZ/3PH



Performance Table

Product Code	m³/s @ Pa (Static)										
	0	100	200	300	400	500	600	700	800	900	1000
ePowerBox EC 50-315-1	0.75	0.67	0.59	0.48	0.25						
ePowerBox EC 50-355-1	1.13	1.04	0.93	0.82	0.66	0.16					
ePowerBox EC 67-400-1	1.34	1.22	1.09	0.91	0.56						
ePowerBox EC 67-450-1	2.03	1.91	1.79	1.66	1.49	1.29	0.98				

Product Code	m³/s @ Pa (Static)											
	0	100	200	300	400	500	600	700	800	900	1000	1100
ePowerBox EC 80-500-3	3.28	3.16	3.05	2.93	2.81	2.69	2.53	2.37	2.19	1.96	1.65	0.56
ePowerBox EC 80-560-3	4.07	3.93	3.76	3.59	3.44	3.27	3.07	2.84	2.54	2.18	1.44	
ePowerBox EC 102-630-3	4.31	4.11	3.86	3.60	3.30	2.93	2.37					
ePowerBox EC 102-710-3	5.25	4.92	4.65	4.32	3.90	3.32	1.90					

Product and Electrical Details


Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers Potentio-meter	Maximum Operating Temp°C	Breakout *Sound Level db(A) (3m)
					Motor (kW)	Full Load Current (A)	Starting Current (A)				
ePowerBox EC 50-315-1	BE315005	1800	Integral	220-240 V/50 Hz/1 Ph	0.25	1.12	1.12	CD3011	0-10 V Pot	50	37
ePowerBox EC 50-355-1	BE355004	1715	Integral	220-240 V/50 Hz/1 Ph	0.46	2.04	2.04	CD3011	0-10 V Pot	40	37
ePowerBox EC 67-400-1	BE400008	1400	Integral	220-240 V/50 Hz/1 Ph	0.46	2.06	2.06	CD3011	0-10 V Pot	40	33
ePowerBox EC 67-450-1	BE450015	1550	Integral	220-240 V/50 Hz/1 Ph	1.03	4.63	4.63	CD3011	0-10 V Pot	40	41

Product Code	Product Number	Speed rpm	Motor Frame	Electrical Supply	Electrical Current			Wiring Diagrams	**Speed Controllers Potentio-meter	Maximum Operating Temp°C	Breakout *Sound Level db(A) (3m)
					Motor (kW)	Full Load Current (A)	Starting Current (A)				
ePowerBox EC 80-500-3	BE500019	1800	Integral	380-420 V/50 Hz/3 Ph	2.69	4.15	4.15	CD3012	0-10 V Pot	60	48
ePowerBox EC 80-560-3	BE560017	1550	Integral	380-420 V/50 Hz/3 Ph	3.1	4.8	4.8	CD3012	0-10 V Pot	50	50
ePowerBox EC 102-630-3	BE630016	1100	Integral	380-420 V/50 Hz/3 Ph	2.39	3.71	3.71	CD3012	0-10 V Pot	60	50
ePowerBox EC 102-710-3	BE710014	940	Integral	380-420 V/50 Hz/3 Ph	2.66	4.13	4.13	CD3012	0-10 V Pot	60	51

*Sound power levels are average dBA at 3 metres distance over sphere, under free field conditions and are presented for comparative purposes only. Values shown are those at the mid-point of the performance curve.

** For speed controllers, please see pages 250-297. For ErP efficiency ratings and grades please refer to our Fan Selector for more information.


Drawings and Dimensions




Product Code	A	B	C	D1	D2	G	Weight Max (kg)
ePowerbox EC 50-315	500	450	450	203	486	409	30
50-355	500	450	450	228	320	409	33
67-400	670	620	620	257	356	579	43
67-450	670	620	620	289	395	579	55
80-500	800	720	720	325	438	659	76
80-560	800	720	720	365	490	659	82
102-630	1020	940	940	410	541	879	113
102-710	1020	940	940	460	605	879	121

Performance charts

ePOWERBOX EC 50-315-1 - UB503159




ePOWERBOX EC 50-355-1 - UB503559




Please note : -
The performances shown are based on the centrifugal 90 degrees discharge, for the axial flow performance please contact our sales team.

ePOWERBOX EC 67-400-1 - UB674059




Performance charts

ePOWERBOX EC 67-450-1 - UB674559




ePOWERBOX EC 80-500-3 - UB805069



Please note :-


The performances shown are based on the centrifugal 90 degrees discharge, for the axial flow performance please contact our sales team.

ePOWERBOX EC 80-560-3 - UB805669




Performance charts

ePOWERBOX EC 102-630-3 - UB106369




ePOWERBOX EC 102-710-3 - UB107169




Please note :-

The performances shown are based on the centrifugal 90 degrees discharge, for the axial flow performance please contact our sales team.

Installation guide




Outdoor installation ePowerBox EC
Axial air flow (900 discharge available)
All accessories supplied seperately




Construction Scheme

Indoor installation:




Outdoor installation:




Wiring Diagrams - ePOWERBOX EC

CD3011



CD3012




BOX FAN

Accessories

A large number of box fan accessories are available which are suitable for connecting to various sizes of ducts, mounting at different locations, both internal and external, and also protecting the fans against extreme weather conditions.

Protection guards, filter with filter boxes and sound attenuators (for rectangular and circular connections) are available for ready supply wherever applicable.





Woods Air Movement delivers smart and energy efficient Air Movement and Fire Safety solutions to support every application area. We offer our customers innovative technologies, high quality and outstanding performance. The widest range of Air Movement and Ventilation products in the market, and strong market presence with over 100 years of experience and manufacturing of products, guarantees that we are always by your side, ready to deliver Excellence in Solutions.

**Contact our friendly sales team today
for more information**

Call: +44 (0) 1206 222 555

Email: quotations.woods@flaktgroup.com
www.woodsairmovement.com

